



Protective clothing

# X-ray protective clothing

## 909 *LytaType* cross back apron

### Features

- > Excellent design transfers weight from the shoulders to the hips.
- > Elasticated flaps fasten at the sides.



Model 909  
Pocket 900/001 shown  
as an optional extra

### Tailor made

- > Tailor made *LytaType* personal x-ray protective clothing is available. Please contact us for required measurements.

### *LytaType* colours and codes


Please note the colours shown are approximate.  
A colour swatch is available on request.



Royal  
02



Navy  
04



Poppy  
11



Silver grey  
40



Bottle Green  
41



Protective clothing

#### Small for chest sizes 80 – 90 cm

Lead equivalent Front and back	Length	Width shoulder	Width hip	Product code
0.25 / 0.25 mm	85 cm	40 cm	60 cm	909/22/085/S
"	90 cm	"	"	909/22/090/S
"	100 cm	"	"	909/22/100/S
"	110 cm	"	"	909/22/110/S
0.35 / 0.25 mm	85 cm	40 cm	60 cm	909/32/085/S
"	90 cm	"	"	909/32/090/S
"	100 cm	"	"	909/32/100/S
"	110 cm	"	"	909/32/110/S
0.50 / 0.25 mm	85 cm	40 cm	60 cm	909/52/085/S
"	90 cm	"	"	909/52/090/S
"	100 cm	"	"	909/52/100/S
"	110 cm	"	"	909/52/110/S

#### Medium for chest sizes 90 – 104 cm

Lead equivalent Front and back	Length	Width shoulder	Width hip	Product code
0.25 / 0.25 mm	90 cm	48 cm	60 cm	909/22/090/M
"	100 cm	"	"	909/22/100/M
"	110 cm	"	"	909/22/110/M
0.35 / 0.25 mm	90 cm	48 cm	60 cm	909/32/090/M
"	100 cm	"	"	909/32/100/M
"	110 cm	"	"	909/32/110/M
0.50 / 0.25 mm	90 cm	48 cm	60 cm	909/52/090/M
"	100 cm	"	"	909/52/100/M
"	110 cm	"	"	909/52/110/M

#### Large for chest sizes 104 – 120 cm

Lead equivalent Front and back	Length	Width shoulder	Width hip	Product code
0.25 / 0.25 mm	90 cm	48 cm	75 cm	909/22/090/L
"	100 cm	"	"	909/22/100/L
"	110 cm	"	"	909/22/110/L
0.35 / 0.25 mm	90 cm	48 cm	75 cm	909/32/090/L
"	100 cm	"	"	909/32/100/L
"	110 cm	"	"	909/32/110/L
0.50 / 0.25 mm	90 cm	48 cm	75 cm	909/52/090/L
"	100 cm	"	"	909/52/100/L
"	110 cm	"	"	909/52/110/L

#### Optional extras: -

Description	Product code
Pocket	900/001
Embroidery in a position to be specified	9/B20