



Protective clothing

X-ray protective clothing

915 *LytaType* jacket (vest)

Features

- > VELCRO® fastened overlapping front provides all round protection.
- > Front doubles the stated protection at an overlap of approximately 15 cm.

Tailor made

- > Tailor made *LytaType* personal x-ray protective clothing is available. Please contact us for required measurements.

LytaType colours and codes


Please note the colours shown are approximate. A colour swatch is available on request.



Royal
02



Navy
04



Poppy
11



Silver grey
40



Bottle Green
41



S Small for chest sizes (A) 80 – 90 cm girth

Lead equivalent (Pb)* Front and back	Length (B)	Maximum girth Waist (C) & hip (D)	Product code
0.25 / 0.25 mm	52 cm	100 cm	915/22/S
0.25 / 0.35 mm	52 cm	"	915/23/S
0.35 / 0.35 mm	52 cm	"	915/33/S

*Pb: Lead vinyl in accordance with BS EN 61331-1:2014 in the 50 to 150 kV range of x-ray tube voltages.

M Medium for chest sizes (A) 90 – 100 cm girth

Lead equivalent (Pb)* Front and back	Length (B)	Maximum girth Waist (C) & hip (D)	Product code
0.25 / 0.25 mm	58 cm	100 cm	915/22/M
0.25 / 0.35 mm	58 cm	"	915/23/M
0.35 / 0.35 mm	58 cm	"	915/33/M

*Pb: Lead vinyl in accordance with BS EN 61331-1:2014 in the 50 to 150 kV range of x-ray tube voltages.



Protective clothing

Ⓛ Large for chest sizes (A) 100 – 120 cm girth

Lead equivalent (Pb)* Front and back	Length (B)	Maximum girth Waist (C) & hip (D)	Product code
0.25 / 0.25 mm	65 cm	120 cm	915/22/L
0.25 / 0.35 mm	65 cm	"	915/23/L
0.35 / 0.35 mm	65 cm	"	915/33/L

*Pb: Lead vinyl in accordance with BS EN 61331-1:2014 in the 50 to 150 kV range of x-ray tube voltages.

Optional extras: -

Description	Product code
Pocket	900/001
Embroidery in a position to be specified	9/B20

Kenex are certified to Regulation (EU) 2016/425 (PPE) for the design and manufacture of x-ray protective clothing. LytaType aprons and thyroid collars comply with the requirements of BS EN 61331-3:2014 and BS EN 13402-3:2013. They include lead (Pb) vinyl material tested for use with a 50 to 150 kV range of x-ray tube voltages, as specified in BS EN 61331-1:2014.

Notified body: SGS UK Ltd, England BS22 OWA. Identification number CE0120.

